




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 1/00, 17/30, H04L 29/06		A1	(11) International Publication Number: WO 98/32066
			(43) International Publication Date: 23 July 1998 (23.07.98)
(21) International Application Number: PCT/GB98/00053 (22) International Filing Date: 9 January 1998 (09.01.98) (30) Priority Data: 97300331.2 20 January 1997 (20.01.97) EP (34) Countries for which the regional or international application was filed: GB et al. (71) Applicant (for all designated States except US): BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): MCGEE, Niall, Gerard [IE/IE]; 20 Stewartstown Park, Belfast, Co Antrim BT11 9GL (GB). (74) Agent: EVERSLED, Michael; BT Group Legal Services, Intellectual Property Dept., Holborn Centre, 8th floor, 120 Holborn, London EC1N 2TE (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: DATA ACCESS CONTROL

(57) Abstract

A modified Web server (310) comprises a session manager (320) which intercepts all incoming requests from clients for Web pages. Each request incorporates a token which the session manager (320) compares with tokens which are stored in a session store (330). Once finding a matching token, a URL associated with the matching token is used by the Web server (310) to return a Web page indicated by the URL to the requester. Any URLs embedded in the Web page to be returned are tokenised by the session manager (320) before the page is returned, and the resulting token/URL pair is stored in the session store (330).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DATA ACCESS CONTROL

The present invention relates to information servers and particularly, but not exclusively, to Internet servers and methods of controlling an Internet server.

5 An important factor which has led to a rapid growth in people and businesses connecting to the Internet is the wealth of information it contains and makes available to practically anyone who has a telephone connection and a personal computer. This strength, however, leads to problems when an information or service provider, which uses the Internet as its communications
10 medium, wishes to control how its information can be accessed.

The information accessible from the Internet is stored on servers which form part of the Internet infrastructure. The information is accessed by clients (which are controlled by users or customers) which are typically connected to, but which are not part of, the Internet. Normally, the clients only connect to the
15 Internet for a relatively short time using, for example, a dial-up modem connection across a telephone line.

While communications and information transfer between Internet clients and servers relies on the well-established TCP/IP protocols, higher-level, dedicated protocols are employed to access certain types of information specific to one of
20 the many services available on the Internet. Different services support different formats of information and allow different types of operation on the information. For example, a Gopher client allows retrieval and display of predominantly text-based information, an FTP (File Transfer Protocol) client supports the transfer between a server and a client of binary or ASCII files and a World Wide Web (or
25 simply a Web) client can retrieve and display mixed text and graphical information, as well as sounds, movies (usually encoded via MPEG), virtual 'worlds', and any other data type for which an appropriate 'viewer' ('helper') application or 'plug-in' is available.

The following description concentrates on the Internet Web service for the
30 purpose of explanation only. The concepts described, however, are more broadly applicable to other Internet services and to other information services available from different communications networks.

Figure 1 illustrates an example of an Internet connection serving a plurality of clients 100 connected via a local area network 110 to a workstation 120. The

workstation 120 is connected via a router 130 and a modem (or ISDN interface) 140 to an Internet connection provider 150. A connection originates from a Web client, for example a Web browser, which is a software process typically residing on a personal computer (PC) or workstation. Using the connection, for example, 5 client 100a can retrieve public information from any Internet server.

In the following description the term Internet server means a physical computing platform which is attached to the Internet, whereas the term Web server means a software process which resides and runs on the physical Internet server to provide the Internet server with Web server functionality. The term 10 server on its own can mean either a Web or an Internet server depending on the context, although the distinction is rarely of significance for the purposes of the following description.

The Web employs a protocol called http (HyperText Transfer Protocol) to support access by a Web browser of information on a Web server. Of course, 15 when transmitted across the Internet, the http information is wrapped in the TCP/IP protocol. The information retrieved by the Web browser is typically an HTML (HyperText Markup Language) file which is interpreted by the browser and displayed appropriately on a display screen as a Web page of information.

The Web browser specifies the information it wishes to retrieve using a 20 URL (Universal Resource Locator) of the form:

`http://Internet server name/server directory/file name,`

where "http" indicates that the URL points to a Web page of information. The 25 Internet server name is translated into a physical network location by the Internet. The server directory is the location on the server of the file and the file name is that of the file in the directory which contains or generates the required information.

Figure 2 is a diagram which illustrates the general form of a typical 30 graphical user interface display provided by a Web browser, for example the Netscape (TM) Navigator Web browser. The display includes several main areas: an options area 200 providing the user-options for controlling and configuring the browser, a Web page display area 210 for displaying a Web page, a location box 220 for displaying the location, or URL, of the displayed Web page, and a status

box 230 which displays information concerning the status of Web page retrieval. Also illustrated on the screen is a pointer 240, the position of which can be controlled by a user using a computer mouse, roller-ball or equivalent pointing device. The user interacts with the browser by positioning the pointer
5 appropriately on the screen and selecting available options or functions provided by the browser or displayed on the Web page by, for example, 'clicking' a mouse button.

An HTML file comprises ASCII text which includes embedded HTML tags. In general, the HTML tags are used to identify the nature and the structure of the
10 Web page, and to identify HyperText links (hyperlinks), which are described in more detail below, and their associated URLs.

The display capabilities of a Web browser determine the appearance of the HTML file on the screen in dependence upon the HTML tags. HTML can in general identify:

- 15 the title of the file;
- the hierarchical structure of the file with header levels and section names;
- bulleted, numbered, and nested lists;
- insertion points for graphics;
- special emphasis for keywords or phrases;
- 20 pre-formatted areas of the file; and
- hyperlinks and associated URLs.

In general, a hyperlink provides a pointer to another file or Internet resource. Sometimes also a hyperlink can point to a different location in a currently-displayed Web page. Within an HTML file, hyperlinks are identified by
25 their syntax, for example:

```
<A HREF="{URL}">{anchor-text}</A>
```

where the < ... > structure identifies the HTML tags.

30 The syntax typically includes a URL, which points to the other file, resource or location, and an anchor definition. In this case, the anchor is defined as a piece of text. In a Web page, typically a hyperlink is represented graphically on screen by the anchor. The anchor can be a piece of highlighted text or an

image, for example a push-button or icon image. Where, for example, the anchor is non-textual, the underlying syntax usually also specifies a respective anchor image file location, which may be on the same or on a different server, as follows:

5

where IMG SRC specifies the location of the image file for the anchor.

The effect of a user selecting a hyperlink, by moving a pointer over the anchor and clicking, say, the mouse button, is normally that the Web browser
10 attempts to retrieve for display as a new Web page the file indicated by the URL. However, sometimes a URL refers to a software process rather than to a Web page per se, as described in more detail below.

In some browsers, for example Netscape (TM) Navigator, when the pointer merely moves over a hyperlink anchor, the browser can be arranged to display the
15 underlying URL in the status box of the display screen, irrespective of whether the user selects the hyperlink or not. Thus, a user can normally see the URL of any hyperlink in a Web page.

HTML files sometimes also include references to other files, for example, graphics files, which are retrieved by the browser and displayed as part of the Web
20 page typically to enhance visual impact. Each reference comprises an appropriate HTML tag and a URL. In practice, the browser retrieves the requested Web page first and then retrieves other files referenced in this way by the Web page. Often, therefore, the textual portions of a Web page appear before the graphical portions.

A user is able to view the ASCII text source code of an HTML file using
25 source code viewing facilities provided by some browsers. Thus, a user is able to view the URLs for any hyperlink or other imported file.

Generally, a user can retrieve a Web page using several methods which are supported by most browsers: by manually entering the URL into the location box, by selecting a Bookmark (the stored URL of a previously-accessed Web page),
30 or by selecting a hyperlink in a displayed Web page. The first two methods potentially allow a user to access any Web page or other resource file at any time. The third method requires the user to first access a Web page which incorporates a hyperlink to the required Web page or image file before that Web page or image file can be retrieved.

In certain circumstances, it would be desirable to limit access by the third method only.

Since, however, a user can normally see any URL embedded in an HTML file and can access a Web page by entering the respective URL directly into a browser, under normal circumstances a service provider has little control over which Web pages are accessed and how they are accessed.

Many servers are arranged to address this problem by employing access tables which include table entries controlling which users can access which pages. An alternative measure, which is widely used, is to employ user identification and password protection to protect certain files on the server. Both measures are open to some degree to "spoofing" by unauthorised persons who have been known to masquerade as an authorised user by, for example, intercepting and cracking passwords for these protected files. A further disadvantage of both measures is the management overhead of keeping access tables or password files up-to-date, particularly where large numbers of users and/or pages are involved, or where the authorised user population changes regularly.

Also, even if Web page access is controlled using access tables or password protection, a service provider normally has no control over the order in which an authorised user can access the Web pages once the URLs are known.

In accordance with one aspect, the present invention provides an information server comprising:

means for receiving a request from a client for an item of information, said item of information including at least one reference to a further item of information;

means for modifying the item of information by replacing the or at least one reference by a token;

means for storing the or each token and each respective reference in storage means; and

means for returning to the client the modified item of information.

An advantage of this aspect of the invention is that the client is not provided with the actual reference information, such as a URL, for the further item(s) of information. Thus, the client would not know the name or location on the information server of the further item(s) of information.

A token preferably comprises a series of digits or other characters. Preferably, a token has a form from which no information about the reference or the respective information item can be derived. In the case of digits, the token may be, for example, generated by a random number generator each time an
5 information item is requested. For a suitably long token number length, therefore, the chances of obtaining the same token more than once for a particular reference are relatively low.

In the following description, it is assumed that any requested item of information includes at least one reference to a further item of information.

10 In accordance with a second aspect, the present invention provides an information server comprising:

means for receiving a request from a client for an item of information, the request including a token indicative of the item of information required;

means for comparing the token with one or more stored tokens to find a
15 matching stored token, each stored token being associated with a corresponding reference to an item of information; and

means for returning to the client, in dependence upon finding a matching stored token, a respective corresponding item of information.

Thus, the information server only returns items of information that can be
20 requested validly by a client, on the basis of a previously-requested item of information. An advantage of this aspect is that the information server can control the order in which items of information can be requested and returned.

In preferred embodiments, where there are a plurality of tokens and respective references stored in association with the information server, and a
25 request includes a valid token, the information server includes means to remove from the store the remaining tokens and respective references. Thus, once one from a selection of available tokens is requested, the remaining, unrequested tokens are removed and thereafter are thus not available for request.

The information server preferably includes means to store with each token
30 and its respective reference the identity of a valid client. Also, in embodiments where multiple clients have access to the information server, the information server includes means to derive from a request for an item of information the identity of the client. Accordingly, a request for an item of information from a

particular client is processed by the information server with respect only to tokens and their respective references having a valid identity.

In a particularly advantageous form, the information server has Web server functionality. Then, a reference may comprise or incorporate a URL. The URL may
5 be part of a hyperlink or, alternatively, it may refer to a further resource, for example an image file intended for display as part of a Web page.

An embodiment of the present invention will now be described, by way of example only, with reference to the accompanying drawings of which:

Figure 1 is a diagram which illustrates a basic Internet connection
10 arrangement;

Figure 2 is a diagram which illustrates the general form of a Web browser;

Figure 3 is a diagram which shows the main components of a Web server modified to operate in accordance with embodiments of the present invention;

Figure 4 is a flow diagram which illustrates the high level process flow of
15 a system according to an embodiment of the present invention;

Figure 5 is a flow diagram which illustrates the process steps for a login procedure;

Figure 6 is a flow diagram which illustrates the process steps for a parsing and tokenising procedure;

20 Figure 7 is a flow diagram which illustrates the process steps for an authentication procedure; and

Figure 8 is a flow diagram which illustrates the generic process steps for building HTML pages.

The embodiment described below is a system for providing customer
25 access to a service provider's major customer service system (MCSS) via the Web. In the present case the service provider is a telephone company such as BT. By accessing and modifying the data held on a database, which in this case is an Oracle (TM) database, of the MCSS, customers of the service provider (especially large corporate clients having extensive and complex communications needs) can
30 order new communications services and manage or configure those services which are already on-line for the client.

Such a system to a high degree removes human error which may arise if customers make demands by telephone or by filling in forms. In particular, in the

case of corporate customers, the system gives the customer a feeling of being in control directly of their service management requirements.

In the past, access to such a system has required dedicated customer or client software running on a workstation located at a customer site, and dedicated
5 dial-up links from the workstation to the system. A major problem associated with such an arrangement is the need to provide, update and maintain client access software.

The present system provides a tailored interface to the service provider's database using a conventional Web browser and Internet connection. The Web
10 server is modified to handle the specific database access requirements, as described in detail below. The system also obviates any need to transfer information from the existing database onto the Web server. In particular, customer login password records, used to control customer access to the database, can therefore remain in the database which is, advantageously,
15 physically separate from the Internet server. Such an arrangement both improves security and helps reduce server file storage capacity requirements.

The system introduces a 'session' framework within which the service provider can control or limit customer access to database facilities. The framework supports customer login and client recognition and authentication.
20 Such a framework is typically included as part of a conventional database access system but is not a conventional aspect of the Web: the Web provides a stateless environment with no maintained connection between the client and server in which there is no framework for controlling data access, apart from possibly password protection for specific files. In particular, the framework enables control over
25 which pages are accessible by which customers, and the order in which a customer can access Web pages. Many of the MCSS transactions require a high volume of information input which it is not possible to fit onto a single Web page. Thus, a number of Web pages are required. These pages form a specific dialogue for specific order types. The information within a dialogue must be collected and
30 sorted so that ultimately a complete order can be placed on the MCSS while dialogues are in use. Thus, a mechanism is required for storing order data from previous Web pages while subsequent Web pages are being interacted with. Also, stored data may affect which data is included in subsequent Web pages. Indeed, the system must generate Web pages dynamically. These Web pages include:

customer specific information (either previously entered or already stored on the MCSS), information relating to previous choices made within a specific dialogue, and default information resulting from previous choices. For example, a communications service ordering transaction may require a customer to enter
5 information into four consecutive data entry screens, or Web pages. Therefore, in this example, controlling which pages can be accessed, and in which order they can be accessed, is important.

Figure 3 is a functional block diagram which illustrates in more detail aspects of an Internet server and the related components of the present system.
10 The Internet server 300 incorporates a Web server 310 for receiving client requests and for transmitting server responses to the requests. The Internet server 300 is a UNIX-based computing platform such as a Sun (TM) SPARCstation 20/51, and the Web server is a Netscape (TM) Enterprise Server modified to operate in accordance with the present system. The Netscape Enterprise Server provides a
15 suitable API (application programming interface) to support such modifications. Of course, other suitable hardware and/or Web server software could be employed instead.

In accordance with the present system, the Web server 310 incorporates a session manager 320. The session manager 320 provides the extra functions
20 necessary for supporting database session management.

The session manager 320 is implemented primarily via use of the Netscape Web Server API (NSAPI) which allows dynamic linking of server functionality from user defined library functions. Thus, the session manager 320 is in effect "built in" to the Web server 310. The session manager 320 intercepts client requests as
25 they traverse the Web server stack and can re-define any of the information contained within the client requests and carry out actions outside of the Web server. The primary tasks enacted by the session manager are:

- manage the number of concurrent user sessions to a pre-defined maximum;
- 30 • allocate free user sessions to new users who are attempting to login;
- associate user sessions with database sessions;
- re-start database sessions which exist or die;
- de-allocate database sessions when a user session times out;

- tokenise URLs;
- resolve requested tokenised URLs; and
- control time-out of user sessions.

A user session, as opposed to a database session, is allocated to a customer as soon as he or she attempts to log into the system from a login Web page. The user session is generated on a per-user basis by picking the next highest (starting at 0) unused session index for that user. The database session is allocated to the customer on gaining MCSS access. The maximum number of user sessions is limited by the number of concurrent processes which the Internet server can manage without performance degrading to below an unacceptable level. Likewise, the maximum number of database sessions is limited to the number of full-time Oracle connections that the MCSS database can support.

A database session is a process which runs on the Internet server and delivers the functionality required to access the MCSS database 390, as described in more detail below.

The session manager 320 has access to a session store 330, a gateway processor 340, a database session controller 350 and an HTML page store 360.

The gateway processor 340 is a task running on a computing platform for processing so-called gateways. Gateways can provide extension mechanisms to the Web server 310 by taking information typically from a source which is not compatible with HTML and converting it into a standard HTML file. In practice, a gateway is a script or program invoked by the Web server 310 via a common gateway interface (CGI) 370 that can accept user input through the Web server 310 and can return HTML, a URL, or some other data back to the client through the Web server 310, or can control further tasks, such as email, which typically provides no return information. Simple gateways may be written in UNIX C-shell and more complex gateways are typically written in a programming language such as C, C⁺⁺ or Java. In practice, a gateway processor such as the gateway processor 340 and a Web server such as the Web server 310 typically reside on a common computing platform. Further information on gateways and the CGI can be found in "Managing Internet Information Services" by Cricket Liu et al, published by O'Reilly & Associates, Inc. ISBN 1-56592-062-7.

The gateway processor 340 has access to a gateway store 380, which holds the gateways necessary for supporting the present system. In the present

system the gateway processes are written in C. The gateway processor 340 also has direct access to the MCSS database 390, the database session controller 350 and the session store 330. The database session controller 350 has access to the session store 330 and to the database 390.

5 The gateway store 380 includes page building gateways for building HTML Web pages based on information retrieved, via the database session controller 350, from the database 390. Many of the page building gateways produce HTML Web pages which include form fields. The form fields are the mechanism by which
10 Web server 310. Customer information retrieved in this way is processed and passed to the database 390 in an appropriate format by respective data processing gateways.

 The gateway store 380 also includes login gateways for controlling who is allowed access to the information in the database 390. The login gateways allow
15 the gateway processor 340 to access the database 390 directly, bypassing the database session controller 350, but only for the purposes of customer authorisation.

 The database session controller 350 is a task running on the Internet server which controls all access to the database 390. The MCSS database 390 is
20 held on a fileserver 395 and comprises customer information stored in database tables on an external storage device such as a hard disk drive (not shown). The hard disk drive is connected to the fileserver 395. Conventionally, customer authorisation is required each time the database 390 is accessed to open an Oracle connection. Such authorisation (for example, providing a user name and password
25 in response to a prompt from the database 390) can take a considerable amount of time (for example, upwards of thirty seconds) especially for access to a remote database 390. In accordance with the system, therefore, the database session controller 350 opens and maintains an Oracle connection with the database 390 for each valid database session, for the duration of the session. Thus, only one
30 initial authorisation step is required to establish the connection and session which has the effect of speeding-up consecutive database 390 accesses via the database session controller 350. When the customer ends a session, the session is closed. The session manager 320 implements a time-out strategy which limits the amount

of time for which an opened session can remain inactive. Beyond this time the session is closed irrespective of whether the customer is using the session or not.

The database 390 contains: customer information such as names, addresses and customer account numbers, customer service information such as the telephone lines allocated to the customer and which services are available from each line, login information, such as encrypted password files, for each customer, and information defining which functions are available to each customer when using the system.

The session store 330 is used for holding session information for a customer during a session. The session information includes information which is stored during a dialogue, for example information provided during a series of data input Web pages. The session information also includes information which controls the Web page flow for multiple Web page transactions. For ease of understanding in the following description, the type of session information created and stored in the session store 330 for Web page flow will now be described with reference to the tables shown below.

<u>Current User</u>
user name
session index
last access time

TABLE 1

<u>Available Page</u>
user name
session index
IP address
real URL
token
referring URL

TABLE 2

<u>Exemptions</u>
URL1
URL2
...
URLn

TABLE 3

A Current User entry, illustrated as Table 1, is created by the session manager 320 and stored in the session store 330 for each customer, or user, when he first gains authorised access to the system. The 'user name' is the name entered by the user during the login procedure, which is described below. The 'session index' is a reference to the user session which is allocated to the user when access to the system is obtained. In practice, the session index is simply a number generated by a counter which increments on a per-user basis. The 'last access time' is the last time the user accessed the database 390 in the allocated

session. If the time between accesses exceeds a pre-determined time-out period, for example 15 minutes, the session is closed.

An Available Page entry, as illustrated by Table 2, is created by the session manager 320 and stored in the session store 330 for each option available
5 to a user from a Web page which is, at the time, displayed by the user's browser. Each Available Page entry corresponds to a URL embedded in the Web page. The 'user name' corresponds to the 'user name' in a Current User entry. The 'session index' corresponds to the 'session index' in a Current User entry. The 'IP address' is the address of the Internet connection of a user's browser (that is to say, the
10 client address). This address is passed in an http header of each message or request sent from the browser to the Web server 310. The 'real URL' is the URL of the Web page referenced by the respective option. The 'token' is a random number which is generated to replace the URL. The token replaces the server directory and the file name portions of the URL which is passed, in the HTML file,
15 back to the browser. The referring URL is the URL of the currently-displayed Web page.

A single Exemptions entry, illustrated as Table 3, is maintained in the session store 330. The exemptions are those URLs which a browser can request and which do not need to be returned by the Web server 310 in tokenised form.
20 That is to say, the actual server directory and file name of the requested Web page are specified in the URL and can be viewed on the browser if desired. In the present embodiment, the only exempted URL which is stored as an exemption is for the login Web page, which is freely returned to any requesting browser.

Figure 4 is a diagram which illustrates the high-level process flow of the
25 present system. As indicated by the flow diagram, there are two possible routes: one route for returning an exempted page, and one route for returning all other pages.

In the following description, unless otherwise stated, all messages from the browser will be treated as a request for a Web page, the particular Web page
30 being specified by a URL. A request may include parameters provided by the user which are passed to the Web server 310 with the URL. The parameters typically effect how the requested Web page is formatted or generated, or which Web page is returned in response to the request.

According to Figure 4, in step 400 the browser establishes a connection with the server. Then, the browser sends a request for a page by forwarding to the server the URL for the page in step 405. The URL is intercepted by the session manager 320.

5 In the case of the request being for the login page (which has an exempted URL), in step 410 the session manager 320 receives the URL, searches the exemptions list and establishes that the login URL is exempted from tokenising. In step 420 the session manager 320 authenticates the request if necessary. For the purposes of login no authentication is required since the login page will be
10 returned to any client. In the present example, the login page is the only exempted page. However, the authentication step is shown to illustrate examples where some form of authentication is required for exempted pages other than the login page.

 In step 430, the session manager 320 retrieves from the HTML page store
15 360 the HTML file for the login page. The HTML file, when displayed on a browser, produces a Web page which includes a submit button and input boxes for the user to enter a name and a password. The submit button is an anchor for a hyperlink having an underlying URL which points to a login gateway stored in the gateway store 380.

20 In the case of the request being for a non-exempted page, that is to say a page other than the login page, in step 410 the session manager 320 receives the URL, searches the exemptions list and establishes that the URL is not exempt from tokenising. Then, in step 415, the request is authenticated, as described in more detail below. Once authenticated, in step 425, either the HTML file for the
25 requested page is retrieved from the HTML page store 360, or a gateway corresponding to the requested URL is retrieved from the gateway store 380 and processed by the gateway processor 340 to produce an HTML file for the requested page. This step will be described in more detail below for the case where the URL refers to the login gateway, which is selected by pressing the
30 submit button on the login page.

 Following step 425 or step 430, the session manager 320 then, in step 435, parses and tokenises the HTML file and replaces the or each URL embedded in the file with a random, ten-digit token. The parsing and tokenising step will be described in greater detail below.

In step 440, the session store 330 is up-dated with the details of the or each tokenised and respective original URL. This step, again, will be described in more detail below.

Finally, the tokenised page is returned to the requesting browser in step
5 445.

The login procedure will now be described with reference to the flow diagram in Figure 5. The login procedure, in relation to Figure 4, occurs in step 425. Accordingly, it is assumed that the user has previously requested the login page, as described above, has provided a name, a password and has clicked on the
10 submit button of the login page to initiate the login procedure. The URL associated with the submit button refers to a gateway stored in the gateway store 380 called "login.cgi". The name and password are passed as parameters with the request for login.cgi using the http POST method. All requests are encrypted automatically by the browser to minimise the possibility of a transmitted URL or password being
15 intercepted and used to access the database 390 by another, fraudulent party. Obviously, the server is provided with the appropriate decryption functionality. The converse is also true—all server responses are encrypted in such a way that the browser is able to de-crypt these. Both encryption and decryption are provided by the SSL (Secure Sockets Layer) protocol.

20 In step 500, in response to receipt of the request for the login.cgi, the session manager 320 generates a user session by allocating the next session index to the user. Then, the session manager 320 signals the gateway processor 340 to execute the login gateway. In doing so, the session manager 320 also passes the name and password to the gateway processor 340. In step 510, the gateway
25 processor 340, under the control of the login gateway, forms a connection with the database 390. Then, the gateway processor 340 passes the user name and password in an appropriate form to the database 390 in step 520 to attempt a login to the database 390. Unsuccessful login, in step 530, is signalled to the gateway processor 340 by the database 390. In response, the gateway processor
30 340 generates an error Web page which is returned to the session manager 320. The session manager 320 in response returns the error Web page to the browser in step 540.

Upon successful log in, signalled appropriately by the database 390, the gateway processor 340, in step 550, initiates the generation of a database session

for the user. The gateway processor 340 achieves this firstly by clearing the connection with the database 390. Then, the gateway processor 340 signals to the database session controller 350 to establish a database session with the database 390 for the, now authorised, user using the same user name and password. The database session controller 350 logs back in to the database 390 and creates a database session. Having created the session, in step 560, the database session controller 350 accesses and up-dates the session store 330 by creating a current user entry which includes the user's name, an allocated session index and the access time (which when accessed subsequently is treated as the last access time)

Having established a database session, in step 570, the gateway processor 340, controlled by the login gateway, generates a 'directive' for the user's browser to cause a warning screen to be displayed. This screen allows a user to abort the login, or continue. If the user chooses to continue, in a step 570, the gateway processor 340 retrieves and executes a process (called homepage.cgi) which obtains customer information provided by the session manager 320, and the database (via the database session controller 350) to generate a specific welcome page for the user. The parameters determine which options are available to the user from the welcome page which is to be generated. Each option forms a hyperlink to a further respective gateway or Web page. The welcome page, in step 580, is then generated on the basis of the parameters. The next step corresponds to step 435 of Figure 4.

The parsing and tokenising step (step 435 of Figure 4) will now be described with reference to Figure 6.

According to Figure 6, the session controller, on receipt of the required HTML file, in step 600, parses (or searches serially from the beginning of) the file to find URLs, or other types of reference to further resources, embedded in the ASCII text of the file. Typically, the URLs which are present refer to Web pages providing further options to the user, or to image files for Web page buttons or images to be incorporated in the Web page to, for example, enhance the visual impact of the Web page. Hereafter, only hyperlink URLs providing further options and image file URLs will be discussed, for reasons of clarity only.

In step 610, a processing loop is established to enact tokenising each time a URL is discovered. In step 620, when a URL is found it is stored in memory. Then, in step 630, a token in the form of a random number is generated using a system call, available on Unix computing platforms, to a function called
5 "elf_hash()". This function is a pseudo-random number generator which takes a null-terminated string and returns a UNIX long integer based on the string. The string used in the elf_hash() call in the present case is a concatenation of:

10 a random number; the user's login name; the user's session index; the requested URL; and the current time.

Such a string will inevitably provide a high probability that the returned integer is unique. However, the returned integer is compared with all other tokens in the session store 330 to check that it is unique. If it is not unique, a new token is
15 generated using elf_hash(), with the random number part of the string concatenation being newly generated. In addition, the generation process pauses for one second to ensure that the current time is different. The elf_hash() function is such that even a small change in the string passed as the parameter can result in a completely different random number being generated. This procedure is repeated
20 until a unique token is generated.

In step 640, the stored URL is modified by replacing the server directory and filename portions of the URL with the token. The 'tokenised' URL is then copied back to the file to replace the original URL.

25 In step 650, a 'Page Option' entry having the form illustrated by Table 2 above is stored in the session store 330.

This procedure is repeated for all URLs which are discovered in the file. Finally, in step 660, the tokenised URLs which are stored in memory are compared with the tokenised URLs of each Page Option entry stored in the session store 330 and having the session index for the user in question. Each Page Option entry not
30 having a corresponding tokenised URL in memory is deemed to be old and no longer representative of a valid user option available from the requested page. Accordingly, each old entry is deleted from the session store 330. This step is equivalent to step 440 of Figure 4 for up-dating the session store 330.

The steps for authentication according to step 415 of Figure 4 will now be described with reference to Figure 7.

According to Figure 7, in step 700, the session manager 320 accesses the session store 330 to match the tokenised URL received as part of the request with a tokenised URL in a Page Option entry. If there is no matching tokenised URL, in step 710, the URL is deemed invalid and in step 730 the session manager 320 initiates the login procedure, as described above, by retrieving the login page HTML file from the HTML page store 360 and returning the file to the requesting browser. The user will then need to login before being allowed to access the database 390. If found, in step 710, further authentication is carried out in step 720 on the basis of the accessing browser's identity. The identity is in the form of an IP address for the browser, which is transmitted by the browser in the header of the request. To be deemed authentic, the IP address must match the IP address stored in the Page Option entry for the respective token. If the IP address is the one present in the Page Option entry, then, in step 740, the real URL for the file is retrieved from the Page Option entry. The real URL points to the required HTML file in the file store, or the gateway in the gateway store 380, requested by the user. If the IP address is invalid, that is to say the IP address does not correspond to the IP address in the respective Page Option entry, then, in step 730, the login procedure is initiated.

The generation of Web pages by page building gateways will now be described with reference to Figure 8.

When, in response to a user request, the gateway processor 340 retrieves a page building gateway from the gateway store 380 (step 425 of Figure 4), according to Figure 8, the gateway processor 340, in step 800, retrieves from the database the information which is to be used for generating the Web page. As described above, some user dialogues, requiring multiple Web pages for information input, require the information input to be stored until the dialogue is complete and an MCSS transaction, on the basis of the information, is enacted. Therefore, in step 810, the gateway processor if necessary accesses the session store 330 to retrieve any prior-input dialogue information which is also to be included in the Web page. Then, in step 820, the HTML file for the Web page is

generated, by well-known procedures, on the basis of the respective information. Subsequently, the procedure continues with step 435 of Figure 4.

The tokens are generated afresh each time a new page is accessed, and then are removed from the session store 330 when the respective option is no longer available. Consequently, even though a user can save or remember a tokenised URL, if the user tries to use it in future, the tokenised URL will not be found in the session store 330. This results in two important implications. Firstly, a user is forced to access pages in a service in a way determined by the service provider - a user cannot select at random any page he chooses, unless the page token/URL pair is in the session store 330. Secondly, no user can access information using someone else's URL. The former implication allows a service provider to control closely how a user accesses pages of information. For example, a service may be an on-line commodity ordering service for which a user needs to provide certain information and specify certain choices for a specific commodity to be ordered satisfactorily. The ordering process may involve a number of different pages to be provided to the user in stages which may vary depending on choices made at each stage. The present embodiment would control closely how the user was able to access the required pages.

In the embodiment described above, user authorisation, by for example providing a username and password, is only required for an initial login page. Authorisation of this kind is not required for any pages accessed from, for example, a welcome page which is provided after the login page.

It is envisaged that the principles embodied in the system could also be employed for other purposes, for example to prevent "in-lining". In-lining is a practice whereby a Web user incorporates hyperlinks in his or her Web pages which point to Web resources generated by other Web users. Typically, in-lining is used to embed other people's Web-based image files into a users own Web pages, thereby utilising the other people's intellectual effort.

In general, embodiments of the inventions provide a database owner such as a service provider with a means to control who has access to information stored in the database and also a means to control how exactly the data is accessed by an authorised accessor.

The skilled person will no doubt be able to arrive at further embodiments, aspects or variants of the invention which also fall within the scope or essence of the present invention.

CLAIMS

1. An information server comprising:
 - means for receiving a request from a client for an item of information, said
 - 5 item of information including at least one reference to a further item of information;
 - means for modifying the item of information by replacing the or at least one reference by a token;
 - means for storing the or each token and each respective reference in
 - 10 storage means; and
 - means for returning to the client the modified item of information.
2. A server according to claim 1, further comprising random number generating means for generating a random number and forming a token on the
- 15 basis of the token.
3. A server according to either preceding claim, further comprising means for storing in association with each token and its respective reference an indication of the identity of the client.
- 20
4. An information server comprising:
 - means for receiving a request from a client for an item of information, the request including a token indicative of the item of information required;
 - means for comparing the token with one or more stored tokens to find a
 - 25 matching stored token, each stored token being associated with a corresponding reference to an item of information; and
 - means for returning to the client, in dependence upon finding a matching stored token, the respective corresponding item of information.
- 30 5. A server according to claim 4, further comprising means for deriving from a request an indication of the identity of the client.

6. A server according to claim 5, further comprising means for comparing the indication of the identity of the client with indications of identity stored in association with each stored token and corresponding reference, and wherein the means for returning operates also in dependence on finding a matching stored indication of identity with the indication of the identity of the client derived from the request.
7. An information server having Web server functionality operable in accordance with the server according to any one of the preceding claims.
8. A method of generating an HTML-formatted document incorporating at least one URL, the method comprising the steps of:
retrieving from a data source data to be formatted in HTML;
forming an HTML-formatted document on the basis of the data;
replacing a URL with a respective token; and
storing in association with a copy of the token a copy of the respective URL.
9. A method of generating an HTML-formatted document incorporating at least one URL, by retrieving from a data source an HTML-formatted document, replacing a URL with a token and storing in association with a copy of the token a copy of the respective URL.
10. An HTML-formatted document generated in accordance with the method of claim 8 or claim 9.
11. An information server having Web server functionality comprising:
means to receive from a requester a request for a Web page;
means to retrieve or generate the requested Web page; and
means to return the Web page to the requester,
the means to retrieve or generate the requested Web page including:
means for replacing a URL in the retrieved or generated Web page with a token; and



means for storing a copy of the token in association with a copy of the replaced URL.

12. An information server having Web server functionality comprising:
- 5 means to receive from a requester a request for a Web page;
means to retrieve or generate the requested Web page; and
means to return the Web page to the requester,
the means to retrieve or generate the requested Web page including:
means for comparing a first identity of the requested Web page with
10 identities stored in a storage means to find a matching second identity; and
means responsive to there being a matching identity to retrieve or
generate for return to the requester a Web page having the second identity, the
second identity being stored in the storage means in association with the first
identity.


- 15 13. A method of controlling an information server to:
- receive a request from a client for an item of information, said item of
information including at least one reference to a further item of information;
modify the item of information by replacing the or at least one reference
20 by a token;
store the or each token and each respective reference in storage means;
and
return to the client the modified item of information.

- 25 14. A method of controlling an information server to:
- receive a request from a client for an item of information, the request
including a token indicative of the item of information required;
compare the token with one or more stored tokens to find a matching
stored token, each stored token being associated with a corresponding reference
30 to an item of information; and
return to the client, in dependence upon finding a matching stored token,
the respective corresponding item of information.


15. A method of controlling an information server comprising the steps of:
establishing a session between a client and the information server;
receiving a request from a client for an item of information, said item of
information including at least one reference to a further item of information;
5 modifying the item of information by replacing the or at least one
reference by a token;
storing the or each token and each respective reference in a store for the
duration of the session; and
returning to the client the modified item of information.
- 10
16. A method of controlling an information server as claimed in Claim 15, in
which, upon receiving a request from a client for an item of information, the
request including a token indicative of the item of information required, the method
further comprises the steps of:
- 15 comparing the token with one or more stored tokens to find a matching
stored token; and
using the corresponding reference to an item of information stored with
said matching stored token in returning the requested information to the client.

**FIGURE 1****FIGURE 2**


2/6

**FIGURE 3**


3/6

**FIGURE 4**



4/6

**FIGURE 5**

5/6

**FIGURE 6**

6/6

**FIGURE 7****FIGURE 8**

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/00053

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G06F1/00 G06F17/30 H04L29/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06F H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	SCHULZRINNE H: "WORLD WIDE WEB: WHENCE, WHITHER, WHAT NEXT?" IEEE NETWORK: THE MAGAZINE OF COMPUTER COMMUNICATIONS, vol. 10, no. 2, 1 March 1996, pages 10-17, XP000580078	1,7,13
Y	see page 11, right-hand column, paragraph 4 see page 12, right-hand column, paragraph 2 - paragraph 3 see page 12, right-hand column, paragraph 5 see page 14, left-hand column, paragraph 1 - paragraph 4	3
A	---	4,8-11, 14,16
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

20 April 1998

Date of mailing of the international search report

25/05/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Powell, D

INTERNATIONAL SEARCH REPORT

Inte 'onal Application No

PCT/GB 98/00053

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	VOELKER G M ET AL: "Mobisaic: an information system for a mobile wireless computing environment" PROCEEDINGS. WORKSHOP ON MOBILE COMPUTING SYSTEMS AND APPLICATIONS (CAT. NO.94TH06734), WORKSHOP ON MOBILE COMPUTING SYSTEMS AND APPLICATIONS, SANTA CRUZ, CA, USA, 8-9 DEC. 1994, ISBN 0-8186-6345-6, 1995, LOS ALAMITOS, CA, USA, IEEE COMPUT. SOC. PRESS, USA, pages 185-190, XP002062592 see abstract see page 185, right-hand column, paragraph 1 - paragraph 2 see page 186, left-hand column, paragraph 5 - page 188, right-hand column, paragraph 1	1,7,13, 15
A	----	4,8-11, 14,16
Y	LEWONTIN S: "THE DCE WEB TOOLKIT: ENHANCING WWW PROTOCOLS WITH LOWER-LAYER SERVICES" COMPUTER NETWORKS AND ISDN SYSTEMS, vol. 27, no. 6, 1 April 1995, pages 765-771, XP000498084 see page 768, left-hand column, line 1 - page 769, right-hand column, line 2	3
A	----	5,6
A	CHU J Y M ET AL: "CREATING A HYPERTEXT MARKUP LANGUAGE DOCUMENT FOR AN INFORMATION SERVER" BEHAVIOR RESEARCH METHODS AND INSTRUMENTATION, vol. 27, no. 2, 1 January 1995, pages 200-205, XP000567305 see the whole document	8-11
A	----	15
A	US 5 528 759 A (MOORE ROBERT E) 18 June 1996 see abstract	
A	DOMEL P: "MOBILE TELESRIPT AGENTS AND THE WEB" DIGEST OF PAPERS OF COMPCON (COMPUTER SOCIETY CONFERENCE) 1996, TECHNOLOGIES FOR THE INFORMATION SUPERHIGHWAY SANTA CLARA, FEB. 25 - 28, 1996, no. CONF. 41, 25 February 1996, INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, pages 52-57, XP000628465	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/00053

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5528759 A	18-06-96	EP 0484261 A	06-05-92
		JP 2549220 B	30-10-96
		JP 7143124 A	02-06-95
<hr/>			